



Max-Pro Plus 15W-40

Premium Diesel Engine Oil
TECHNICAL DATA SHEET

Product Description:

Veedol Max-Pro Plus 15W-40 is premium diesel engine oil specially developed by combination of premium quality base oils and selected additives meeting API CI-4 specifications along with many industrial and OEM specifications.

Veedol Max-Pro Plus 15W-40 provides maximum protection to modern generation turbocharged/ supercharged diesel engines and possesses very high thermal and oxidation stability property.

Performance Specifications:

Meets & Exceeds performance requirements of

- API CI-4/ SL
- ACEA E7-16
- Global DHD-1
- Deutz DQC III-10
- JASO DH-1
- MB 228.3
- Volvo VDS-3
- Mack EO-M Plus/ EO-N
- Cummins CES 20078
- MTU 2.0
- MAN M 3275
- Renault RLD-2
- Caterpillar ECF-1a
- DDC 93K215

Features/Benefits:

- Ensures engine durability under adverse conditions that may stress wear control
- High temperature stability, excellent oxidation resistance
- Provides optimum protection against wear, rust & corrosion.
- Specially formulated for use in on-highway, off-road steady speed applications in large diesel engines

Application:

Suitable for engines designed to meet Euro IV/III/II norms.

Recommended for use in various manufacture's of diesel engines like Cummins, Caterpillar, MAN, Komatsu, Volvo, Hino, Deutz, Tata Motors, Toyota, Ashok Leyland, Mahindra, Force Motors, Eicher Motors and other Turbocharged high performance diesel engines.

Typical Properties:

Test Parameter	ASTM Test Method	Typical Values
Kinematic Viscosity, @ 100°C, cSt	ASTM D 445	14.7
Viscosity Index	ASTM D 2270	145
Flash Point (COC), °C	ASTM D 92	240
Pour Point, °C	ASTM D 97	- 36
CCS Viscosity @-20°C, mPa.s	ASTM D 5293	5100

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.